



**DFE series fixed incounter dispensers**

- Four fixed guides with 'flat' guide top
- Models to suit round plates 160-338 millimetres diameter
- Capacity of approximately 55-60 plates
- Multispring mechanism to give easy adjustment for different plate weights
- Heated models with 400W element and 70 °C thermostat
- Lids available in polycarbonate and stainless steel
- Available with brass flange
- Option for heated units to be thermostatically heated by remote (up to 1500 mm) thermostat, mounted in bezel

**General specification** DFE incounter heated plate dispenser, with four fixed guides. Circular flange with 'flat' guide tops. Capacity of approximately 55-60 round plates. Multispring mechanism to give easy adjustment for different plate weights. Generally finished in stainless steel. Heated units with heating element of 400W, located in base, controlled by fixed 70°C thermostat. No switch or neon. Supplied with cable and plug. Operates from 230V - 50HZ - 1PH electric supply. Option for heated units to be thermostatically controlled by remote (up to 1500mm) thermostat, mounted in bezel. Bezel cut out 148 high mm x 86 mm wide. All dimensions in millimetres. All dimensions in millimetres.

<u>Product code</u>	<u>Plate diameter</u>	<u>Cutout diameter</u>	<u>Flange diameter</u>	<u>Depth below counter</u>
01.1210.02 unheated	145-160	243	254	235
01.1323 unheated	160-205	288	300	655
01.1333 unheated	190-240	318	330	655
01.1343 unheated	230-280	358	370	655
01.1353 unheated	260-310	388	400	655
01.1363 unheated	290-338	418	430	655
03.1713 heated	160-205	288	300	675
03.1723 heated	190-240	318	330	675
03.1733 heated	230-280	358	370	675
03.1743 heated	260-310	388	400	675
03.1753 heated	290-338	418	430	675

\* These cutout diameters apply to counter tops up to 2 mm thick. It is permissible to increase the diameter of the cutout by up to 4 mm to facilitate fitment of the dispenser in thicker counter tops.