



#### Mobile plate dispenser

- Available in one or two stack configuration, heated or unheated
- Plate capacity approximately 55-60 plates per stack
- Heated units are thermostatically controlled, with on off switch and heavy duty spiral cable
- Double skin and mineral wool insulation to heated units
- Fitted with push bar, corner bumpers and four 125mm diameter castors, two braked

#### Product code

1TN-MS210, 2TN-MS210, 1THN-MS210, 2THN-MS210  
1TN-MS240, 2TN-MS240, 1THN-MS240, 2THN-MS240  
1TN-MS280, 2TN-MS280, 1THN-MS280, 2THN-MS280  
1TN-MS310, 2TN-MS310, 1THN-MS310, 2THN-MS310

#### Plate diameter

160-210 mm  
190-240 mm  
230-280 mm  
260-310 mm

General specification Equalizer mobile plate dispenser, with four fixed guides. Capacity of approximately 55-60 round plates per stack. Multispring mechanism to give easy adjustment for different plate weights. Generally finished in stainless steel. Heated units are double skinned and insulated and fitted with an adjustable 30-120°C thermostat and on/off switch. Fitted with push bar with heat insulated mountings, corner bumpers and four 125mm diameter castors, two braked and heavy duty spiral cable with plug and plug holder. Electric loading of 500W to one stack unit, 1600W to two stack unit. Operates from 230V - 50HZ - 1PH electric supply. Dimensions: one stack 520 x 485 x 910 mm, two stack 920 x 485 x 910 mm, over corner buffers, excluding push bar.