



Heated incounter soup well

- Capacity approximately 10 litres
- Thermostatically controlled by remote thermostat
- Supplied with lift out inner soup pot and hinged lid
- Option of lift out inner soup pot with two handles for easy movement between kitchen and servery, and lockable hinged lid
- Option of bezel back box to facilitate installation of control bezel
- Includes drain kit which we strongly recommend be fitted

<u>Product code</u>	<u>Description</u>	<u>Cutout diameter</u>	<u>Flange diameter</u>	<u>Depth</u>
08.2057V	Heated incounter soup well with drain kit. Complete with soup pot hinged lid with ladle notch.	274 mm	312 mm	260 mm
08.2057	Heated incounter soup well with drain kit. Complete with soup pot with handles and lockable hinged lid with ladle notch.	274 mm	312 mm	260 mm

General specification Heated incounter soup well with drain kit. Capacity approximately 10 litres. Thermostatically controlled by remote (up to 1500mm) thermostat, mounted in bezel. Bezel cutout 148 high mm x 86 mm wide. Overall incounter dimensions 260 mm (320 mm with drain valve) high x 312 mm diameter. Supplied with lift out soup pot and hinged lid with ladle notch. Fitted with cable and plug. Electric load of 400W. Operates from 230V - 50HZ - 1PH electric supply. Includes drain kit which we recommend be installed to facilitate cleaning.