



T(H) series adjustable incounter dispensers

- With three adjustable guide rods
- Models to suit round plates 150-290 millimetres diameter
- Capacity of approximately 55-60 plates
- Multispring mechanism to give easy adjustment for different plate weights
- Heated models with 400W element, 70°C thermostat and rocker switch
- Option for heated units to be thermostatically heated by remote (up to 1500 mm) thermostat, mounted in control panel

General specification Incounter plate dispenser. With three adjustable guide rods mounted through circular flange, with 'flat' guide tops. Capacity of approximately 55-60 plates. Multispring mechanism to give easy adjustment for different plate weights. Generally finished in stainless steel. Heated units with heating element of 400W, located in base, controlled by fixed 70°C thermostat. Fitted with rocker switch and neon protected from ingress of moisture by a neoprene cap. Supplied with cable and plug. Operates from 230V - 50HZ - 1PH electric supply.

Note: Option for heated units to be thermostatically controlled by remote (up to 1500mm) thermostat, mounted in control panel. Control panel cut out 148 high mm x 86 mm wide. All dimensions in millimetres.

<u>Product code</u>	<u>Plate diameter</u>	<u>Cutout diameter</u>	<u>Flange diameter</u>	<u>Depth below counter</u>
T245 unheated	150-220	306	317	650
T280 unheated	180-260	342	359	650
T310 unheated	210-290	370	382	650
TH245 heated	150-220	306*	317	670
TH280 heated	180-260	342*	359	670
TH310 heated	210-290	370*	382	670

* These cutout diameters apply to counter tops up to 2 mm thick. It is permissible to increase the diameter of the cutout by up to 4 mm to facilitate fitment of the dispenser in thicker counter tops.